Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Withdrawn) A method for obtaining hydrogen, comprising:
 - passing a fuel gas stream over an anode to create an anode effluent stream; and
 - obtaining a hydrogen gas stream from at least a portion of the anode effluent stream.
- 2. (Withdrawn) The method according to claim 1 wherein the hydrogen gas stream is obtained using a hydrogen membrane.
- 3. (Withdrawn) The method according to claim 1 wherein the anode comprises part of a first fuel cell stack.
- 4. (Withdrawn) The method according to claim 3 wherein the fuel cell stack comprises a dual chamber stack.
- 5. (Withdrawn) The method according to claim 3 wherein the fuel cell stack comprises a single chamber stack.
- 6. (Withdrawn) The method according to claim 3 further comprising: storing the hydrogen gas stream in a hydrogen storage device.
- 7. (Withdrawn) The method according to claim 6 wherein the hydrogen storage device comprises a metal hydride bed.

- 8. (Withdrawn) The method according to claim 6 further comprising: passing the stored hydrogen from the integrated storage device over the anode during start-up of the first fuel cell stack.
- (Withdrawn) The method according to claim 6 further comprising: passing the stored hydrogen from the integrated storage device over a second anode during start-up of a fuel cell stack.
- 10. (Withdrawn) The method according to claim 9 wherein the second anode is either (i) a second anode in the first fuel cell stack or (ii) an anode in a second fuel cell stack.
- 11. (Withdrawn) The method according to claim 1 further comprising; a heating step for heating the fuel gas stream prior to being passed over the anode.
- 12. (Withdrawn) The method according to claim 1 further comprising:

 passing at least a portion of the fuel gas stream through a temperature

 control unit prior to being passed over the anode.
- 13. (Withdrawn) The method according to claim 13 wherein the temperature control unit is a heat exchanger.
- 14. (Withdrawn) The method according to claim 12 wherein heat is at least partially provided by passing at least a portion of the anode effluent through the temperature control unit.
- 15. (Withdrawn) A method for operating a fuel cell, comprising: passing hydrogen from an integrated storage unit over an anode during start-up; and

- replenishing the stored hydrogen by passing a hydrogen gas stream into the storage unit;
- wherein the hydrogen gas stream is obtained from an anode effluent stream.
- 16. (Withdrawn) The method according to claim 15 wherein the hydrogen storage unit comprises a metal hydride bed.
- 17. (Withdrawn) The method according to claim 15 wherein the hydrogen gas stream is obtained using a hydrogen generation unit.
- 18. (Withdrawn) The method according to claim 17 wherein the hydrogen generation unit comprises a hydrogen membrane.
- 19. (Withdrawn) The method according to claim 15 further comprising passing at least a portion of the anode effluent through a temperature control unit.
- 20. (Withdrawn) A method for heating a fuel cell, comprising:

 passing an oxygen containing gas over an active material in a hydrogen

 storage unit to create an exothermic reaction heat source; and

 conveying the heat from the exothermic reaction to the fuel cell.
- 21. (Withdrawn) The method according to claim 20 wherein the active material comprises metal hydride material.
- 22. (Withdrawn) The method according to claim 20 wherein the active material comprises a metal selected from the group consisting of Pd, Pt, Ru, Rh and Ni.
- 23. (Withdrawn) The method according to claim 20 wherein the active material comprises Pd.

- 24. (Withdrawn) The method according to claim 20 wherein the active material comprises a hydrogen oxidation catalyst.
- 25. (Withdrawn) The method according to claim 20 further comprising; passing at least a portion of the oxygen containing gas through a temperature control unit.
- 26. (Withdrawn) The method according to claim 25 wherein the temperature control unit is a heat exchanger.
- 27. (Currently amended) A fuel cell system, comprising:
 - a fuel cell stack producing an anode effluent stream; and
 - a hydrogen generation unit configured to produce a hydrogen gas stream from the anode effluent stream of the fuel cell stack;
 - a hydrogen storage unit into which at least a portion of the produced hydrogen gas stream is stored; and
 - a structure coupled to said hydrogen storage unit that heats said fuel cell stack by promotinges an exothermic reaction using hydrogen from said hydrogen storage unit, wherein heat from said exothermic reaction heats said fuel cell stack to speed up fuel cell startup.
- 28. (Original) The system according to claim 27 wherein the hydrogen storage unit comprises one or more mechanisms selected from the group consisting of metal hydride bed, hydrogen sorption material, and compressed gas bottle.
- 29. (Previously presented) The system according to claim 27 wherein the structure comprises a metal hydride.
- 30. (Original) The system according to claim 27 wherein the hydrogen generation unit comprises a hydrogen separation membrane.

- 31. (Original) The system according to claim 27 further comprising a temperature control unit.
- 32. (Original) The system according to claim 31 wherein the temperature control unit is a heat exchanger.
- 33. (Canceled).
- 34. (Original) The system according to claim 27 further comprising: a hydrogen means for providing additional power during high load on the fuel cell stack.
- 35. (Canceled).
- 36. (Currently amended) A fuel cell system, comprising:
 - a fuel cell stack; and
 - a means for obtaining hydrogen from an anode effluent stream of the fuel cell stack;
 - a means for storing said hydrogen; and
 - a means for heating said fuel cell stack [[to]] and for speeding up fuel cell startup.
- 37. (Original) The system according to claim 36 wherein the means for hydrogen storage comprises a metal hydride.
- 38. (Original) The system according to claim 36 wherein the means for obtaining hydrogen comprises hydrogen separation membrane.
- 39. (Canceled).

Appl. No. 10/629,066 Amdt. dated February 13, 2007 Reply to Office Action of November 13, 2006

- 40. (Original) The system according to claim 36 further comprising a temperature control unit.
- 41. (Original) The system according to claim 36 wherein the temperature control unit is a heat exchanger.
- 42. (Canceled).
- 43. (Original) The system according to claim 36 further comprising: a hydrogen means for providing additional power during high load on the fuel cell stack.
- 44. (Canceled).